

American Thermal Products

Tel: 408-686-0460 Fax: 408-686-0462 Email: sales@medlandandassociates.com

It's Simply COOL!

AC 120x120x38mm

- Housing: Aluminum Painted.
- Blade: Plastic UL 94V-O P.B.T.
- Insulation Resistance: 100M Ohm min, 500VDC between wire and frame
- Dielectric Strength: 1800VAC for two second between lead and frame / 500micronamps maximum leakage.
- Operation Temp: -20 °C ~ 85 °C
- Weight: 510g



Specification:

Part Number	Bearing Availability	Rated Voltage (VDC)	Air Flow (CFM)	Speed (RPM)	Static Pressure (mmH ₂ O)	Rated Current (mA)	Power (W)	Noise (dBA)	Life Hour (25°C)
FA1238B11T7C-31	2 Ball or Sleeve	120V (60Hz)	134.0	3,150	10.6	200	16.0	46.0	50,000
FA1238B11T7-61			110.0	3,000	8.2	220	16.5	44.0	50,000
FA1238B11T5-61			100.0	2,700	7.4	200	12.6	43.0	50,000
FA1238B11T3-61			93.0	2,400	6.0	180	11.0	40.0	50,000

For Wire lead version, change "T" in the part number to "W".

For 230V version, change "11" in the part number to "22".

For Sleeve Bearing version, change "B" in the part number to "S". Life Hour: 30,000 (25°C).

