

American Thermal Products

Tel: 408-686-0460 Fax: 408-686-0462 Email: sales@medlandandassociates.com

It's Simply COOL!

AC 172x150x51mm

- Housing: Aluminum Painted.
- Blade: Plastic UL 94V-O P.B.T.
- Insulation Resistance: 100M Ohm min, 500VDC between wire and frame
- Dielectric Strength: 1800VAC for two second between lead and frame / 500micronamps maximum leakage.
- Operation Temp: -20 °C ~ 85 °C
- Weight: 960g



Specification:

Part Number	Bearing Availability	Rated Voltage (VDC)	Air Flow (CFM)	Speed (RPM)	Static Pressure (mmH ₂ O)	Rated Current (mA)	Power (W)	Noise (dBA)	Life Hour (25°C)
FA1751B11T7C-31	2 Ball	120V (60Hz)	293.0	3,300	20.0	400	38.00	57.0	50,000
FA1751B11T7-61	2 Ball or Sleeve		216.0	2,900	13.0	600	38.00	57.0	50,000
FA1751B11T5-61			209.0	2,600	10.0	500	32.00	53.0	50,000
FA1751B11T3-61			195.0	2,300	8.0	400	26.00	50.0	50,000

For Wire lead version, change "T" in the part number to "W".

For 230V version, change "11" in the part number to "22".

For Sleeve Bearing version, change "B" in the part number to "S". Life Hour: 30,000 (25°C).

