

American Thermal Products

Tel: 408-686-0460 Fax: 408-686-0462 Email: sales@medlandandassociates.com

It's Simply COOL!

DC 30x30x10mm

- Housing / Blade: Plastic UL 94-O P.B.T.
- Insulation Resistance: 10M Ohm, 500VDC/min between bare wire and frame
- Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
- Operation Temp: -10 °C ~ 70 °C (Humidity 35%-85% RH)
- Lead Wire: UL 1570 #28 AWG
- Weight: 9g



Specification:

Part Number	Bearing Availability	Rated Voltage (VDC)	Air Flow (CFM)	Speed (RPM)	Static Pressure (mmH ₂ O)	Rated Current (mA)	Power (W)	Noise (dBA)	Life Hour (25°C)
FD3010B05W3	2 Ball	5	2.5	5,800	1.8	70	0.35	19.0	80,000
FD3010B05W5			2.9	6,800	2.6	90	0.45	22.5	80,000
FD3010B05W7			3.5	7,800	3.0	110	0.55	25.0	75,000
FD3010B12W3		12	2.5	5,800	1.8	70	0.84	19.0	80,000
FD3010B12W5			2.9	6,800	2.6	80	0.96	22.5	80,000
FD3010B12W7			3.5	7,800	3.0	90	1.08	25.0	75,000

