

American Thermal Products

Tel: 408-686-0460 Fax: 408-686-0462 Email: sales@medlandandassociates.com

It's Simply COOL!

DC 40x40x28mm

- Housing / Blade: Plastic UL 94-O P.B.T.
- Insulation Resistance: 10M Ohm, 500VDC/min between bare wire and frame
- Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
- Operation Temp: -10 °C ~ 70 °C (Humidity 35%-85% RH)
- Lead Wire: UL 1007 #26 AWG
- Weight: 40g



Specification:

Part Number	Bearing Availability	Rated Voltage (VDC)	Air Flow (CFM)	Speed (RPM)	Static Pressure (mmH ₂ O)	Rated Current (mA)	Power (W)	Noise (dBA)	Life Hour (25°C)
FD4028B12W7	2 Ball	12	11.3	8,500	10.6	130	1.56	35.0	75,000
FD4028B12W9-R			12.6	10,000	13.6	200	2.40	41.0	75,000
FD4028B12W11-R			14.7	11,500	18.0	260	3.12	44.0	75,000
FD4028B24W7		24	11.3	8,500	10.6	80	1.92	35.0	75,000
FD4028B24W9-R			12.6	10,000	13.6	100	2.40	41.0	75,000
FD4028B24W11-R			14.7	11,500	18.0	145	3.48	44.0	14.7

